



- 9-, 12-, 15-, 18-, 24, 36, 48-Stations
- Wall- or Pedestal-Mount

With the highest surge protection in its price range, the Toro® Custom Command offers durability and performance in one rugged commercial-grade controller.



Learn more at toro.com

Features & Benefits

Versatile Runtimes

Run times from one minute to ten hours in one-minute increments meet the needs of standard or drip applications.

Independent Programs

Four fully independent programs and 16 start times that can run concurrently with start time overlap protection within each program.

High Surge Protection

Highest surge protection in its price range for lightning-prone areas.



Water Management Highlight



Wired RainSensor or Wireless Rain/Freeze sensors will stop irrigation when it rains or when temperature drops below a user-defined point.



EPA WaterSense® approved
when used with Irritrol®
Climate Logic®



Specifications

Dimensions

- 292 x 149 x 219mm (11½" x 5⅞" x 8⅝") W x H x D
- Weight: 3,6 kg (8 lbs)

Electrical Specifications

- Input Power
 - 120 VAC, 60 Hz or 230 VAC, 50 Hz
 - 50VA
- UL, CUL Listed
- Station output power
 - 24 VAC (60 Hz)
 - 0,50 amps (12 VA) per station maximum
 - 0,50 amps (12 VA) pump/master valve
 - 1,25 amps (30 VA) total load

Operating Specifications

- Three selectable watering schedules:
 - Seven-day calendar
 - Odd/even days with day exclusion
 - 31-day interval
- 365-day calendar with automatic compensation for leap year
- Rain delay from one to seven days
- Program stacking for simultaneous operation of one to four programs
- Season % Adjust by month
- Individual station manual start and manual start by program
- Independent program erase for each program
- Master valve/pump start operation selectable by program
- Available in 9-, 12-, 15-, 18-, 24-, 36- and 48-station models
- Non-volatile memory retains programmed information in event of power failure
- Self-diagnostic circuit breaker that identifies and overrides faulty stations

Optional Accessories

- TRS: Wired RainSensor
- 53853: Wired Rain/Freeze Sensor
- TWRS/TWRFS: Wireless RainSensor or Rain/Freeze Sensor

Warranty

- Five years



High-Surge Protection

With the highest surge protection in its competitive price range, a self-diagnostic circuit breaker and a five-year warranty, this controller withstands the test of time.

Custom Command Series 230 VAC Model List

Wall-Mount Plastic Cabinet	
Model	Description
CC-P9-50H	9-station
CC-P12-50H	12-station
CC-P15-50H	15-station
CC-P18-50H	18-station
CC-P24-50H	24-station
Wall-Mount Metal Cabinet	
CC-M24-50H	24-station
CC-M36-50H	36-station
CC-M48-50H	48-station

Specifying Information—Custom Command

CC-PXX-XXX				
Model	Cabinet	Description		Power
CC	P	XX		XXX
CC—Custom Command	P—Plastic M—Metal	9—9-stations 12—12-stations 15—15-stations	18—18-stations 24—24-stations 36—36 stations 48—48 stations	(blank)—120 VAC/60Hz 50H—230 VAC/50Hz
Example: A 12-station Custom Command Controller with an internal transformer and metal cabinet would be specified as: CC-M12				

toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

Printed in U.S.A.
©2016 The Toro Company.
All Rights Reserved.
GB 200-XXXXNA Electronic file only.



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.